

## Classic softshell jacket in sporty design made of recycled polyester

Pleasantly soft 3-layer function material with TPU-membrane Wind- and waterproof (5,000 mm water column), breathable and permeable to water vapour Seams not sealed Inside made of micro fleece, mesh lining in the front Stand-up collar 2 side pockets and 1 breast pocket with zips Full-length under-panel 2-way zip with chin cup Elastic cord on hem for width-adjustment Zips: YKK JN1171: lightly waisted

# Fabric:Outer fabric (290 g/m²): 100%<br/>polyester (recycled)<br/>Lining: 100% polyesterCountry of origin:Bangladesch

61023090

Care instructions:

Customs tariff number:



Partner article:



Men's Softshell Jacket Art-Nr.: JN1172

Available colours

	XS	S	М	L	XL	XXL		
Weight in g	535 g	550 g	585 g	620 g	655 g	695 g		
VPE	1/20	1/20	1/20	1/20	1/20	1/20		
(Pcs. per inner packaging								
/ pcs. per outer packaging								

Measurements in cm	XS	S	М	L	XL	XXL
1/2 chest	48,00 cm	50,00 cm	52,00 cm	56,00 cm	60,00 cm	64,00 cm
1/2 bottom width	50,00 cm	52,00 cm	54,00 cm	58,00 cm	62,00 cm	66,00 cm
front length from	61,00 cm	62,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm
shoulder						
length back from	63,00 cm	64,00 cm	66,00 cm	68,00 cm	70,00 cm	72,00 cm
shoulder						
sleeve length	60,00 cm	61,00 cm	62,00 cm	63,00 cm	63,00 cm	63,00 cm

Available colours





graphite (432C) red (200C)

#### Features



**OEKO-TEX®** Standard 100

OEKO-Tex® CONFIDENCE IN TEXTILES STANDARD 100 15.0.70467 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100

#### Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



#### **Recycled Polyester**

PET bottles are recycled to create a new fashion. Plastic bottles are crushed, melted down and spun to yarn again, which is sometimes completely integrated into the production.



### Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

Stand: 02.05.2024 - 07:45:06