



Functional 3-layer fleece jacket


3-layer functional fabric with TPU membrane
 Wind- and water-proof (5,000 mm water column), breathable and permeable to vapour (2,000 g/m²/24h)
 Non-taped seams
 Full-length storm flap, elastic cord with stoppers on hem
 2 zipped concealed pockets
 JN1006: Breast pocket
 JN1007: Slightly waisted
 Middle layer: water-proof, breathable and wind-proof TPU membrane

Fabric: Outer fabric (350 g/m²): 100% polyester
 Lining: 100% polyester

Country of origin: Volksrepublik China

Customs tariff number 61023090

Care instructions



Partner article



Men's Bonded Fleece Jacket
 Art-Nr.: JN1006

Available colours

	S	M	L	XL	XXL
Weight in g	542g	588g	635g	693g	716g
VPE (pcs. per inner packaging / pcs. per outer packaging)	1/10	1/10	1/10	1/10	1/10
measurements in cm	S	M	L	XL	XXL
1/2 chest:	47,00 cm	51,00 cm	55,00 cm	59,00 cm	63,00 cm
1/2 waist width:	43,00 cm	47,00 cm	51,00 cm	56,00 cm	60,00 cm
1/2 bottom width:	49,00 cm	53,00 cm	57,00 cm	61,00 cm	65,00 cm
front length from shoulder:	63,00 cm	65,00 cm	67,00 cm	69,00 cm	71,00 cm
length back from shoulder:	67,00 cm	69,00 cm	71,00 cm	73,00 cm	75,00 cm
sleeve length incl. shoulder:	73,00 cm	74,00 cm	75,00 cm	76,00 cm	77,00 cm

Available colours

■ aqua/navy (7461C, 5395C)
 ■ green/navy (583U, 5395C)
 ■ red/carbon (201C, 447U)

■ black/red (blackC, 201C)
 ■ navy/red (296C, 201C)

■ carbon/black (425C, blackC)
 ■ orange/carbon (716U, 425C)



Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m² within 24 hours. The higher this figure, the more breathable the textile is.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.