



### TEXTILES

cotton  
cotton mix

as well as other natural fibres



### REQUIREMENTS

minimum detail strength  
positive: 0.3 mm, negative: 0.6 mm  
(feed)

vector file  
or pixel graphics with 300 dpi

minimum quantity  
50 pcs.



### APPLICATION

temperature: 170-185 °C  
Preheating is not necessary

time: 8-12 seconds

pressure: 0.5-0.8 kp/cm<sup>2</sup>  
3-4 bar (strong pressure)



### CARE

washable up to 60°C  
iron inside out  
do not chlorinate  
do not tumble-dry  
do not dry-clean



### CERTIFICATE

tested for harmful substances  
Oeko-Tex Standard 100 Class 1  
suitable for babies and toddlers



### SHELF LIFE

approx. 6 months if kept airtight  
in a dark environment

TRANSFER PRINTING

# D3000

SATIN FINISH & OPAQUE

The D3000 transfer convinces with an extremely **soft, textile touch** and a **satın finish, a sporty yet elegant look**. Due to its **high opacity** it is perfectly suited for **dark and light textiles**. It can be applied on cotton and mixed fabrics, **gently on the textile**. Another feature is its **high elasticity**.

The D3000-transfer is suitable for **all backgrounds** (light, coloured or dark, cotton and mixed fabrics).



### CHARACTERISTICS

gentle on the textile (from 160 °C)  
soft touch  
high elasticity and opacity  
satın finish  
suitable for babies and toddlers

